

### 3M ESPE

#### Imprint<sup>®</sup> 4

- ① Vinyl Polystyrene Admonterial
- ② Materiale per stampa ad a base di fosforo
- ③ Materiale di supporto di polipropilene (PPS)
- ④ Materiale di stampa



Information per l'uso  
Istruzioni de utilizaze  
Instrucciones de utilizaze



#### ENGLISH

**Product description**  
The product is a two part casting resin for dental use. It is used to produce dental models, impressions, wax patterns for lost wax casting, etc. It is used to produce dental models, impressions, wax patterns for lost wax casting, etc. It is used to produce dental models, impressions, wax patterns for lost wax casting, etc.

Product	Volume	Weight	Color	Ratio	Mixing Time (min)	Setting Time (min)
Impprint 4	100 ml	100 g	White	1:1	15	20
Impprint 4	100 ml	100 g	White	1:1	15	20
Impprint 4	100 ml	100 g	White	1:1	15	20
Impprint 4	100 ml	100 g	White	1:1	15	20

**Preparation**  
The resin is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener.

**Application**  
The resin is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener.

**Storage**  
The resin should be stored in a cool, dry place. It should be stored in a cool, dry place. It should be stored in a cool, dry place. It should be stored in a cool, dry place.

**Technical specifications**  
The resin has a viscosity of 150-200 cP. It has a viscosity of 150-200 cP. It has a viscosity of 150-200 cP. It has a viscosity of 150-200 cP.

**Storage and stability**  
The resin is stable for 12 months. It is stable for 12 months. It is stable for 12 months. It is stable for 12 months.

**Customer information**  
Please contact your distributor for more information. Please contact your distributor for more information. Please contact your distributor for more information.

Product	Volume	Weight	Color	Ratio	Mixing Time (min)	Setting Time (min)
Impprint 4	100 ml	100 g	White	1:1	15	20
Impprint 4	100 ml	100 g	White	1:1	15	20
Impprint 4	100 ml	100 g	White	1:1	15	20
Impprint 4	100 ml	100 g	White	1:1	15	20

**Technical specifications**  
The resin has a viscosity of 150-200 cP. It has a viscosity of 150-200 cP. It has a viscosity of 150-200 cP. It has a viscosity of 150-200 cP.

**Application**  
The resin is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener.

**Preparation**  
The resin is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener.

**Storage**  
The resin should be stored in a cool, dry place. It should be stored in a cool, dry place. It should be stored in a cool, dry place. It should be stored in a cool, dry place.

**Storage and stability**  
The resin is stable for 12 months. It is stable for 12 months. It is stable for 12 months. It is stable for 12 months.

**Customer information**  
Please contact your distributor for more information. Please contact your distributor for more information. Please contact your distributor for more information.

Product	Volume	Weight	Color	Ratio	Mixing Time (min)	Setting Time (min)
Impprint 4	100 ml	100 g	White	1:1	15	20
Impprint 4	100 ml	100 g	White	1:1	15	20
Impprint 4	100 ml	100 g	White	1:1	15	20
Impprint 4	100 ml	100 g	White	1:1	15	20

**Technical specifications**  
The resin has a viscosity of 150-200 cP. It has a viscosity of 150-200 cP. It has a viscosity of 150-200 cP. It has a viscosity of 150-200 cP.

**Application**  
The resin is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener.

**Preparation**  
The resin is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener.

**Storage**  
The resin should be stored in a cool, dry place. It should be stored in a cool, dry place. It should be stored in a cool, dry place. It should be stored in a cool, dry place.

**Storage and stability**  
The resin is stable for 12 months. It is stable for 12 months. It is stable for 12 months. It is stable for 12 months.

**Customer information**  
Please contact your distributor for more information. Please contact your distributor for more information. Please contact your distributor for more information.

Product	Volume	Weight	Color	Ratio	Mixing Time (min)	Setting Time (min)
Impprint 4	100 ml	100 g	White	1:1	15	20
Impprint 4	100 ml	100 g	White	1:1	15	20
Impprint 4	100 ml	100 g	White	1:1	15	20
Impprint 4	100 ml	100 g	White	1:1	15	20

**Technical specifications**  
The resin has a viscosity of 150-200 cP. It has a viscosity of 150-200 cP. It has a viscosity of 150-200 cP. It has a viscosity of 150-200 cP.

**Application**  
The resin is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener.

**Preparation**  
The resin is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener.

**Storage**  
The resin should be stored in a cool, dry place. It should be stored in a cool, dry place. It should be stored in a cool, dry place. It should be stored in a cool, dry place.

**Storage and stability**  
The resin is stable for 12 months. It is stable for 12 months. It is stable for 12 months. It is stable for 12 months.

**Customer information**  
Please contact your distributor for more information. Please contact your distributor for more information. Please contact your distributor for more information.

Product	Volume	Weight	Color	Ratio	Mixing Time (min)	Setting Time (min)
Impprint 4	100 ml	100 g	White	1:1	15	20
Impprint 4	100 ml	100 g	White	1:1	15	20
Impprint 4	100 ml	100 g	White	1:1	15	20
Impprint 4	100 ml	100 g	White	1:1	15	20

**Technical specifications**  
The resin has a viscosity of 150-200 cP. It has a viscosity of 150-200 cP. It has a viscosity of 150-200 cP. It has a viscosity of 150-200 cP.

**Application**  
The resin is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener.

**Preparation**  
The resin is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener. It is used in a 1:1 ratio with the hardener.

**Storage**  
The resin should be stored in a cool, dry place. It should be stored in a cool, dry place. It should be stored in a cool, dry place. It should be stored in a cool, dry place.

